

Technical Sheet		BC-33A-35		Nitta Corp. of America		
				06/25/2001		
ITEM		DESCRIPTION				
Belt Specs	Structure	<p>PVC (green) - 35° shore A</p> <p>6.0 mm</p> <p>PVC layer</p> <p>Polyester Fabric (white)</p>				
	Anti-Static	YES				
Manuf. Standard	Size	Width: 2000 mm	78 in			
		Length: 100 m	328 ft			
Belt Properties	Tensile Strength	210 N/mm	1200 lbs/in			
	Elongation at Break	10 %				
	Standard Tension	0.5 %				
	Working Load at 1%	18 N/mm	103 lbs/in			
	Min. Pulley Diameter	Finger Joint :	Ø150 mm	6.0 in		
		Skiver Joint :	Ø200 mm	7.9 in		
	Temperature Range	Continuously:	-10 to +70 °C	14 to 158 °F		
		Periodically :	-20 to +100 °C	-4 to 212 °F		
	Coefficient of Friction (Steel)	top:	over 1.0			
		bottom:	0.2 to 0.25			
Weight	6.8 kg/m ²	1.39 lbs/ft ²				
Special Properties						

Phone: (800) 221-3689

www.nitta.com

Fax: (770) 623-1398